

欧司朗光触媒LED灯泡

LED LIGHT SHIELD BULB



无可视
频闪

无蓝光
危害



欧司朗光触媒LED灯泡

LED LIGHT SHIELD CLA BULB



产品优势

- 采用朗德万斯独家Light Shield光触媒技术，持续高效杀灭病菌
- 空气净化功能，有效去除甲醛等有毒有害气体
- 安全科技，对人和动物无害
- 无可视频闪
- 无蓝光危害
- 相比欧司朗白炽灯节能85%以上，绿色环保省电
- 可靠品质源自德国百年照明品牌

产品特性

- 发光角度 200°
- 光效最高可达 95lm/w
- 15,000 小时超长寿命
- 瞬时全亮，无需等待
- 无汞，无紫外红外

安装指南:

- 室内环境使用
- 更换灯泡前请先切断电源
- 输入电压: 220-240V
- 频率: 50-60HZ
- 不可调光
- 不可在密闭或紧凑的灯具中使用
- 储存温度和湿度范围 (-20°C ~ +80°C, 最大湿度 95%)
- 工作温度和湿度范围 (-20°C ~ +30°C, 最大湿度 95%)
- 用以更换的LED灯泡的重量可能会明显大于被更换的灯泡。灯泡重量的增加可能会降低某些配件和灯座的机械稳定性，并可能影响接触的完整性以及灯泡的固定。

Lamp conformity

- IEC 62560 Self-ballasted LED-lamps for general lighting services by voltage > 50 V – Safety specifications
- IEC 62471/ GB/T20145 Photo biological safety of lamps. Meet RG0 requirement
- EN 55015 Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
- EN 61000-3-2 Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
- EN 61000-3-3 Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
- EN 61547 Equipment for general lighting purposes - EMC immunity requirements

废弃处理建议






- 带有WEEE标识的产品可以在固定收集点被回收。
- LED 灯必须按照特种垃圾来处理



欧司朗皓亮LED灯泡


LED LIGHT SHIELD CLA BULB



Item name	Product number (EAN)	W ¹		lm ¹	K	Ra	 ²	 ¹	 ¹	 ³	
CLA40	04.04.01.003.0185	5.5	E27	470	2700	80	NO	200	95	55	15000
CLA40	04.04.01.003.0186	5.5	E27	470	6500	80	NO	200	95	55	15000
CLA60	04.04.01.003.0189	8.5	E27	806	2700	80	NO	200	113	60	15000
CLA60	04.04.01.003.0213	8.5	E27	806	6500	80	NO	200	113	60	15000
CLB25	04.04.01.003.0184	3.3	E14	250	2700	80	NO	180	100	37	15000
CLB40	04.04.01.003.0218	5.5	E14	470	4000	80	NO	220	100	37	15000
CLB40	04.04.01.003.0219	5.5	E14	470	6500	80	NO	220	100	37	15000
CLP25	04.04.01.003.0187	3.3	E27	250	2700	80	NO	200	80	45	15000
CLP25	04.04.01.003.0188	3.3	E27	250	6500	80	NO	200	80	45	15000


Tc 温度

5.5W & 8.5W



Tc Max: ≤95°C

3.3W & 5.5W



Tc Max: ≤95°C

3.3W



Tc Max: ≤95°C